SENSILITE




SENSILITE

SENSILITE

Shimano redesigned the Sensilite A rod series to be lightweight, sensitive, and versatile in key finesse trout and panfish situations. With ultra-light and light powers and limber actions across the series, Sensilite A rods are perfect for fishing streams, docks or ponds. The durable yet lightweight blank construction provides enhanced sensitivity and features Aluminum Oxide guides for increased durability. A custom reel seat with a cork insert provides maximum in-hand comfort, and the quality full-grip cork handles offer anglers a high-end feel at an affordable price.









SENSILITE													
Length	Power	Action	Mono Line Rating (lb test)	PP Line (lb. test)	Lure Rating (oz.)	Foregrip Length (in)	Grip Length (in)	Guide Type	Pieces	Grip Material	UPC	MSRP	
6'0"	L	F	4-8	4-15	1/16-1/4	1	7	Aluminum Oxide	1	Cork	022255143974	\$49.99	
7′0″	L	XF	4-8	4-15	1/16-1/4	1	9	Aluminum Oxide	1	Cork	022255143950	\$49.99	
5'6"	UL	F	2-6	3-10	1/32-3/16	1	5	Aluminum Oxide	1	Cork	022255143967	\$49.99	
6'6"	UL	F	2-6	3-10	1/32-3/16	1	7	Aluminum Oxide	1	Cork	022255143981	\$49.99	
8'0"	L	MF	4-8	4-15	1/16-1/4	1	9	Aluminum Oxide	2	Cork	022255143998	\$54.99	
	6'0" 7'0" 5'6"	6'0" L 7'0" L 5'6" UL	6'0" L F 7'0" L XF 5'6" UL F 6'6" UL F	Rating (lb test) 6'0" L F 4-8 7'0" L XF 4-8 5'6" UL F 2-6 6'6" UL F 2-6	Rating (lb test) 6'0" L F 4-8 4-15 7'0" L XF 4-8 4-15 5'6" UL F 2-6 3-10 6'6" UL F 2-6 3-10	Rating (lb test) 6'0" L F 4-8 4-15 1/16-1/4 7'0" L XF 4-8 4-15 1/16-1/4 5'6" UL F 2-6 3-10 1/32-3/16 6'6" UL F 2-6 3-10 1/32-3/16	Rating (lb test) 6'0" L F 4-8 4-15 1/16-1/4 1 7'0" L XF 4-8 4-15 1/16-1/4 1 5'6" UL F 2-6 3-10 1/32-3/16 1 6'6" UL F 2-6 3-10 1/32-3/16 1	Rating (lb test) 6'0" L F 4-8 4-15 1/16-1/4 1 7 7'0" L XF 4-8 4-15 1/16-1/4 1 9 6'6" UL F 2-6 3-10 1/32-3/16 1 5 6'6" UL F 2-6 3-10 1/32-3/16 1 7	Rating (lb test) 6'0" L F 4-8 4-15 1/16-1/4 1 7 Aluminum Oxide 7'0" L XF 4-8 4-15 1/16-1/4 1 9 Aluminum Oxide 5'6" UL F 2-6 3-10 1/32-3/16 1 5 Aluminum Oxide 6'6" UL F 2-6 3-10 1/32-3/16 1 7 Aluminum Oxide	Rating (lb test) 6'0" L F 4-8 4-15 1/16-1/4 1 7 Aluminum Oxide 1 7'0" L XF 4-8 4-15 1/16-1/4 1 9 Aluminum Oxide 1 5'6" UL F 2-6 3-10 1/32-3/16 1 5 Aluminum Oxide 1 6'6" UL F 2-6 3-10 1/32-3/16 1 7 Aluminum Oxide 1	Rating (lb test) 6'0" L F 4-8 4-15 1/16-1/4 1 7 Aluminum Oxide 1 Cork 7'0" L XF 4-8 4-15 1/16-1/4 1 9 Aluminum Oxide 1 Cork 6'6" UL F 2-6 3-10 1/32-3/16 1 5 Aluminum Oxide 1 Cork 6'6" UL F 2-6 3-10 1/32-3/16 1 7 Aluminum Oxide 1 Cork	Rating (lb test) 6'0" L F 4-8 4-15 1/16-1/4 1 7 Aluminum Oxide 1 Cork 022255143974 7'0" L XF 4-8 4-15 1/16-1/4 1 9 Aluminum Oxide 1 Cork 022255143950 5'6" UL F 2-6 3-10 1/32-3/16 1 5 Aluminum Oxide 1 Cork 022255143967 6'6" UL F 2-6 3-10 1/32-3/16 1 7 Aluminum Oxide 1 Cork 022255143981	